

# Puma Extra 5W-40 SN

## Semi-Synthetic Engine Oil

Puma Extra 5W-40 SN is a semi synthetic lubricant that exceeds performance of mineral lubricants, due to its advanced technology in which the lubricant adheres tenaciously to all surfaces, and resists removal from extreme pressure areas, even when the engine is shut down, ensuring adequate protection at start up.

- ✓ Anti-wear Protection
- ✓ Oxidation Resistance
- ✓ Anti-foam Performance

## Designed to Perform

### Anti-wear Protection – Longer Equipment Life

Proven anti-wear additive packages provide greater resistance to sliding wear thus ensuring efficiency and long life of all moving parts, which greatly reduces the need for engine servicing and overhauls.

### Multi-grade Performance

Suitable for all year use, in most climatic conditions. An enhanced viscosity index improver allows for the engine oil to give excellent protection during cold start-ups and extremely hot conditions.

### Oxidation Resistance - Longer Oil Life

It has extremely good oil life and lubricant stability even when subjected to unusually high thermal stresses; this property minimises sludge and deposit formation, thus preventing blocking of ports, valves and controls, while guaranteeing that the oil remains properly fluid. Maintenance costs are therefore reduced and the useful service life of the oil is extended.

### High Detergency – Increased Engine Cleanliness

It has excellent detergency properties, making it particularly suitable for use in supercharged engines. It also has high dispersant properties. The lubricant is thus very resistant to the formation of lacquer and varnish, as well as sludge and other engine deposits. It helps prevent ring sticking and keeps pistons clean, while maintaining soot deposits in suspension ready to be filtered.

### Antifoam – Increased Performance

Easy release of entrained air which will prevent difficulties with pumps and controls which can cause irregularities in performance and other problems arising from the compressibility of air bubbles.

### Fuel Saving Properties

The fuel saving properties allow for a reduction in fuel consumption compared to traditional lubricants.

### Low Pour Point - Easy Start Up

Allows for easy start-up of engines, even at low temperatures.

### Anti-corrosion & Anti-rust Properties

It has particularly good anti-corrosion properties which effectively protect the engine from corrosion from combustion moisture and acids. These additives inhibit the oxidation of internal surfaces of the engine and therefore prevent breakdown of the oil.

### Demulsibility – Engine Life Extension

Prevents the formation of water in oil emulsion, which enters the system through leakage or condensation. The fluids therefore maintain their lubricating power and anti-corrosion performance even under these circumstances.

### Applications

Puma Semi Synthetic Technology is a semi synthetic and multi-grade premium lubricant. Recommended for gasoline engines from American, European, Asian OEMs. For use in passenger cars and light duty trucks with turbo charged petrol and diesel engines or direct injection engines operating under the maintenance procedures recommended by the manufacturer. Keeps engine lubricated under any condition.

## Puma Extra 5W-40 SN

Approvals:

- API SN

Meets:

- VW 502 00, 505 00, 505 01
- ACEA C3-10, A3/B4-04
- MB 229.31
- FORD WSS-M2C917A
- BMW Longlife-04
- Renault RN0700, RN0710
- Porsche A40
- Dexos2 (Opel GM LL-A025, GM LL-B025)

## Typical Physical Characteristics

Property	Temp	Units	Test Methods	Extra 5W-40
Viscosity Grade	-	SAE	-	5W-40
Kinematic Viscosity	40°C	cSt	ASTM D445	86.5
Kinematic Viscosity	100°C	cSt	ASTM D445	13.58
Viscosity CCS	-25°C	cP	ASTM D5293	6080
Viscosity Index	-	-	ASTM D2270	160
Total Base No	-	mg KOH/g	ASTM2896	7.3
Flash Point (COC)	-	°C	ASTM D92	230
Pour Point	-	°C	ASTM D97	-42
Density	20°C	g/mL	ASTM 1250	0.8516

*These characteristics are typical of current product methods whilst future production will conform to Puma Lubricants specifications, variations in these physical characteristics may occur.*

## Health & Safety Environment

- This product is unlikely to present any significant health and safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with eyes and skin, use proper impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on health and safety is available on the appropriate Safety Data Sheet (SDS) which can be obtained from [sds.pumaenergy.com.au](https://sds.pumaenergy.com.au)

## Protect the Environment

- Take used oil to an authorised collection point. Do not discharge used or new oil into drains, soil or water.

## Additional Information

- Technical advice may be obtained from your Puma Energy Representative.